



#### DESCRIPTION

150 cm self-adhesive membrane made of Extra Waterproofing Membrane. It's consisting of PP/PU/PP/A/P layers that can be directly applied to the walls and the floors without using additional sealing products to ensure waterproofing.



#### TECHNICAL DATASHEET

Product Name	EXTRA PLUS+
Composition	PP/PU/PP/A/P
Size of Roll ( W x L )	1.00 m x 30 m
Recommended Working Temperature	+15 °C / + 35 °C
Temperature Resistance	+10 °C / + 60 °C
Warranty	5 years product warranty
Certification	EN 13859-1
Storage	It can be stored for 12 months in a dry environment between +15 °C / + 25 °C without exposure to sunlight.

PHYSICAL PROPERTIES	TEST METHOD	RESULT	TOLERANS
Weigth	EN 1849-2	380 g/m2	+/- 10 g/m2
Width	EN 1848-2	150 cm	+/- 2 cm
Standart Roll Length	EN 1848-2	30 m	+/- 1 m
Standart Roll Weight	-	18.0 kg/roll	+/- 0,5 kg
Water Penetration Resistance	TS EN 1928	W1 Class	-
Water Vapour Diffusion Resistance (Sd)	TS EN 1931	>6	-
Reaction to Fire	TS EN 11925-2	E Class	-

\*The values above are only for information purpose, cannot be used as a official document.