



DESCRIPTION

Three layers waterproofing and damp-proofing membrane used under tiles. Consisting of PP/PE/PP layers that protects floor and wall substrates from water penetration and moisture passage in wet areas.



TECHNICAL DATASHEET

Product Name	MAXI
Composition	PP/PE/PP
Size of Roll (L x W)	1.00 m x 30 m
Resistance to Temperature	-10 °C / + 60 °C
Warranty	5 years product warranty
Certification	EN 13859-1
Storage	It should be stored in cool and dry area without exposing sunlight

PHYSICAL PROPERTIES	TEST METHOD	RESULT	TOLERANS
Weight	EN 1849-2	220 g/m ²	+/- 10 g/m ²
Width	EN 1848-2	100 cm	+/- 2 cm
Standart Roll Length	EN 1848-2	30 m	+/- 1 m
Standart Roll Weight	-	7.00 kg/roll	+/- 0,5 kg
Water Penetration Resistance	TS EN 1928	W1 Class	-
Transversal Resistance to Tearing (Nail Shank)	TS EN 12310-1	85 N	+/- 30 N
Longitudinal Resistance to Tearing (Nail Shank)	TS EN 12310-1	95 N	+/- 25 N
Transversal Tensile Resistance	TS EN 12311-1	395 N/5cm	+/- 30 N/5cm
Longitudinal Tensile Resistance	TS EN 12311-1	455 N/5cm	+/- 40 N/5cm
Longitudinal Elongation	TS EN 12311-1	70 %	+/- 6 %
Elongation at Break	TS EN 12311-1	70 %	+/- 8 %
Water Vapour Diffusion Resistance (Sd)	TS EN 1931	>60	-
Reaction to Fire	TS EN 11925-2	E Class	-

*The values above are only for information purpose, cannot be used as a official document.