



DESCRIPTION

Three layers self-adhesive waterproofing and damp-proofing membrane used under tiles. Durable and soft waterproofing membrane composed of PES/PE/PES/A/P layers.



TECHNICAL DATASHEET

Product Name	ULTRA
Composition	PES/PE/PES/A/P
Size of Roll (W x L)	1.00 m x 30 m
Recommended Working Temperature	+15 °C / + 35 °C
Resistance to Temperature	+10 °C / + 60 °C
Warranty	5 years product warranty
Certification	EN 13859-1
Storage	It can be stored for 12 months in a dry environment between +15 °C / + 25 °C without exposure to sunlight.

PHYSICAL PROPERTIES	TEST METHOD	RESULT	TOLERANS
Weigth	EN 1849-2	420 g/m2	+/- 10 g/m2
Width	EN 1848-2	100 cm	+/- 2 cm
Standart Roll Length	EN 1848-2	30 m	+/- 1 m
Standart Roll Weight	-	13.50 kg/roll	+/- 0,5 kg
Water Penetration Resistance	TS EN 1928	W1 Class	-
Water Vapour Diffusion Resistance (Sd)	TS EN 1931	>60	-
Reaction to Fire	TS EN 11925-2	E Class	-

*The values above are only for information purpose, cannot be used as a official document.